



# GTAccess Limited

GTAccess Limited



THE ACCESS SPECIALISTS



**ACCESS ALLIANCE**  
Together we've got it covered.

**0 3 3 0 3 3 3 4 8 4 8**\*

t: 01527 871123  
email [info@gtaccess.co.uk](mailto:info@gtaccess.co.uk)  
or visit [www.gtaccess.co.uk](http://www.gtaccess.co.uk)

The easy & affordable solution for all your access requirements

\*Standard rates apply



See pages  
7-18 for our  
full product  
range




Hire

call **0 3 3 0 3 3 3 4 8 4 8** or visit **www.gtaccess.co.uk**

**GTAccess** have one of the most up to date hire fleets currently available for rental, and are one of the largest privately owned access companies in the UK.

We currently operate over 40 individual types of machines, giving us the ability to offer the safest and most cost effective solution for your requirements.



Together we've got it covered.

#### **National Coverage**

GTAccess are not only able to cover your local requirements, but also your National requirements through our partners within the Access Alliance. So call us no matter where your need is for powered access throughout the UK.

#### **Site surveys**

GTAccess are able to offer **free** site surveys, so you never need to worry whether you have ordered the correct machine. Please call your local depot to arrange a convenient time.

#### **Safety Harnesses**

Both IPAF and the HSE recommend that a full restraint type harness with an adjustable lanyard is worn whenever operating any form of boom lift (1b, 3b categories). These can be hired very competitively from GTAccess. If requested, we can deliver at the same time as your hire machine saving unnecessary postage costs.

#### **We get there on time... every time**

Our up to date transportation includes articulated and fixed bed Lorries, and is backed up by 4x4 vehicles and trailers for a cost effective and speedy service.

All vehicles are tracked so precise delivery times can be promised, and more importantly, achieved.

#### **Engineering Back-up**

All depots have dedicated service engineers who are fully trained in all of our platforms. Backed up with dedicated vehicles and trailers and parts stock, we aim to achieve a first fix repair every time the need arises. Cover is available 7 days a week.

#### **GTA All Risk**

Under the model terms and conditions of the Construction Plant Hire Association the hirer is responsible for all damage repair and losses costs. For a small percentage of the weekly hire charge, we are able to provide our GTA All Risk package.



## Sales

call **0 3 3 0 3 3 3 4 8 4 8** or visit [www.gtaccess.co.uk](http://www.gtaccess.co.uk)

**GTAccess** can supply all of your requirements in a very cost-effective way, so why hire when purchasing is sometimes the logical option to reduce your outgoings.

A host of payment options are available on powered access platforms that include Hire Purchase, Contract Hire and Finance Lease Plans.

### Powered Access

As an independent distributor and not being manufacturer tied, you can be assured that we will offer you the platform that best suits your requirements as opposed to what best suits us.

We are able to supply all manner of powered access platforms including self-propelled scissor lifts, self-propelled boom lifts, trailer mounted towable units, mast booms and a whole variety of specialist access platforms, so you can be assured that we will have a unit to match your specification and budget.

We are also able to supply a range of used equipment for those that prefer this option.

### Safety Harnesses

Both IPAF and the HSE both recommend that a full restraint type harness with an adjustable lanyard in worn whenever operating any form of boom lift (1b, 3b categories). These can be purchased from your local GTAccess depot.







## Training

**FACT:** It is the employers responsibility to ensure that all employees are given adequate training for the task in hand.

With over 30 years experience with access equipment, GTAccess are able to determine which of our packages best suits your individual requirements.

Please refer to the individual plans to ascertain your need, or call any of our depots for their experienced opinion.

Training can be undertaken at any of our depots, including the dedicated training suite at our Bromsgrove training centre, your offices, or on site in certain circumstances. All operatives will receive a pass certificate on successful completion of the course, normally valid for five-years.

Though specialising in training related to the access industry, we are also able to offer courses covering such topics as Emergency First Aid, Ladder & Steps, Craning, Securing Loads, Materials Handling to name but a few. Contact any of our experienced personnel where they will be pleased to discuss your individual requirements.





call **0 3 3 0 3 3 3 4 8 4 8** or visit [www.gtaccess.co.uk](http://www.gtaccess.co.uk)

### High Demand Courses Delivered:

IPAF Scissor & Boom Operator Training:

- Static 1a - Scissor that must be used without riggers
- Static 1b - Boom
- Mobile 3a - Scissor
- Mobile 3b - Boom
- MEWP's for Managers
- IPAF Harness Training
- Emergency First Aid at Work

### Other popular courses available:

- IPAF Mentoring for Instructors
- IPAF Train the Trainer
- PASMA Aluminium Scaffold Training course
- PASMA Low-level Course
- Ladder & Steps Training
- Risk Assessment in the workplace
- COSHH
- Safety Awareness
- Basic Health & Safety
- Site Safety Awareness
- Safety for Senior Executives
- Safety for Line Managers
- Specialist Slinging



Follow us on Facebook - GTAccess Ltd • Check out our Facebook & Twitter pages for last minute booking deals! •



Twitter @gtaccessltd



## Service

call **03303334848** or visit **[www.gtaccess.co.uk](http://www.gtaccess.co.uk)**

**GTAccess** is able to offer front line service packages on all manufacturers access platforms.

With over 30 years experience with powered access platforms, there is very little that we have never worked on. Working from all our depots, our engineers aim for a quick response time to get you up & running in the shortest time possible.



### Service plan options

To be as flexible as possible GTAccess offers the four individually tailored plans shown. The plans are available on any manufacturers machine of any age, though an initial chargeable inspection may be required if the unit is not currently under a GTAccess Service Plan.

### Which level of Service best suits you?

#### BRONZE SERVICE PLAN

Covers your statutory LOLER inspections.

The Health and Safety states in the Code of Practice Regulation 10, "In the case of lifting equipment for lifting persons, testing MUST occur at least every 6 months by trained personnel".

#### SILVER SERVICE PLAN

As Bronze plan, but includes two services on your platform.

All consumable items used will be charged at applicable end-user rate.

#### GOLD SERVICE PLAN

As Silver plan, but includes up to four call-outs for unscheduled repairs, should a breakdown occur.

Includes all consumable parts used during service visit. Any parts used outside service consumables will be charged at applicable end-user rate.

#### PLATINUM SERVICE PLAN

As Gold plan, but also includes unlimited call-outs for unscheduled repairs.

Includes all parts\*, both consumables used on service and any parts used for all repairs.

This is the choice for those wanting complete peace of mind and no unexpected surprises.



This range of machines are designed to be used ideally in narrow internal applications.



## Ultra Compact Electric Scissor Lifts

## 4.0m - 6.5m working heights

	X3 or POP-UP 8		X3S or POP-UP 10		GR15		SJ16		GR20	
Battery	✓		✓		✓		✓		✓	
Non-Marking Tyres	✓		✓		✓		✓		✓	
4x4 Rough Terrain	✗		✗		✗		✗		✗	
Levelling Capability	✗		✗		✗		✗		✗	
Narrow	✓		✓		✓		✓		✓	
Reach Height	4.5 m	14' 8"	5.0 m	16' 3"	6.47 m	21' 3"	6.75 m	22' 2"	8.07 m	25' 11"
Platform Height	2.5 m	8' 2"	3.0 m	9' 8"	4.47 m	14' 6"	4.75 m	15' 7"	6.07 m	19' 11"
Stowed Height Closed	1.7 m	6' 0"	1.8 m	6' 0"	1.57 m	5' 2"	1.79 m	5' 11"	1.98 m	6' 6"
Length	1.2 m	4' 0"	1.3 m	4' 3"	1.35 m	4' 5"	1.37 m	4' 7"	1.35 m	4' 5"
Width	0.7 m	2' 5"	0.8 m	2' 6"	0.75 m	2' 6"	0.76 m	2' 6"	0.8 m	2' 8"
Platform Size	1.1 x 0.7 m	3'7" x 2'4"	1.1 x 0.7 m	3'7" x 2'4"	0.89 x 0.75 m	2'11" x 2'6"	0.69 x 0.93 m	2'4" x 3'1"	0.89 x 0.75 m	2'11" x 2'6"
Platform Size Ext.	n/a	n/a	n/a	n/a	1.4 x 0.75 m	4'7" x 2'6"	n/a	n/a	1.4 x 0.75 m	4'7" x 2'6"
Weight	370 Kgs	815 lbs	385 Kgs	849 lbs	994 Kgs	2191 lbs	966 Kgs	2129 lbs	1112 Kgs	2451 lbs
Lifting Capacity	240 Kgs	529 lbs	240 Kgs	529 lbs	227 Kgs	500 lbs	227 Kgs	500 lbs	159 Kgs	350 lbs





This range of machines are designed to be used ideally in narrow internal applications. In certain circumstances, some machines can also be used externally from a solid and level standing.



## Electric Scissor Lifts

	SJ3219		SJ3226		SJ4626		MEC3259	
Battery	✓		✓		✓		✓	
Non-Marking Tyres	✓		✓		✓		✓	
4x4 Rough Terrain	✗		✗		✗		✓	
Levelling Capability	✗		✗		✗		✓	
Narrow	✓		✓		✓		✓	
Reach Height	7.8 m	25' 7"	9.9 m	34' 6"	9.9 m	32' 6"	11.75 m	38' 0"
Platform Height	5.8 m	19' 0"	7.9 m	25' 11"	7.9 m	25' 11"	9.75 m	32' 0"
Stowed Height Closed	1.6 m	5' 3"	1.9 m	3' 3"	1.8 m	5' 11"	2.09 m	6' 11"
Length	1.8 m	5' 11"	2.3 m	7' 7"	2.3 m	7' 7"	2.67m	8' 9"
Width	0.8 m	2' 8"	0.8 m	2' 8"	1.2 m	4' 0"	1.5 m	4' 11"
Platform Size	1.6 x 0.7 m	5'3" x 2'4"	2.1 x 0.7 m	6'11" x 2'4"	2.1 x 1.1 m	6'11" x 3'8"	1.17 x 2.31 m	3'10" x 7'7"
Platform Size Ext.	2.5 x 0.7 m	8'3" x 2'4"	3.0 X 0.7 m	9'11" x 2'4"	3.3 x 1.1 m	10'10" x 3'8"	1.17 x 3.39 m	3'10" x 11'2"
Weight	1312 Kgs	2893 lbs	1890 Kgs	4167 lbs	2170 Kgs	4785 lbs	3150 Kgs	6950 lbs
Lifting Capacity	227 Kgs	500 lbs	227 Kgs	500 lbs	454 Kgs	1001 lbs	340 Kgs	750 lbs





## 8.0m - 17.0m working heights

	SJ4632		COMPACT 14 or GS4047		GS4069		153-12	
Battery	✓		✓		✓		✓	
Non-Marking Tyres	✓		✓		✓		✓	
4x4 Rough Terrain	✗		✗		✗		✗	
Levelling Capability	✗		✗		✓		✗	
Narrow	✓		✓		✓		✓	
Reach Height	11.8 m	38' 0"	13.8 m	45' 3"	14.2 m	46' 6"	17.3 m	56' 6"
Platform Height	9.8 m	32' 0"	11.8 m	38' 8"	12.2 m	40' 0"	15.3 m	50' 0"
Stowed Height Closed	1.9 m	6' 3"	1.88 m	6' 2"	2.8 m	9' 1"	2.7 m	8' 9"
Length	2.5m	8' 2"	2.45 m	8' 1"	3.1 m	10' 2"	4.1 m	13' 5"
Width	1.2 m	4' 0"	1.2 m	4' 0"	1.75 m	5' 9"	1.2 m	3' 9"
Platform Size	2.2 x 1.2 m	7'2" x 4'0"	2.4 x 1.1 m	7'10" x 3'9"	2.9 x 1.7 m	10'0" x 5'8"	3.9 x 1.2 m	12'7" x 4'0"
Platform Size Ext.	3.3 x 1.2 m	10'8" x 4'0"	3.4 x 1.1 m	11'12" x 3'9"	3.8 x 1.7 m	13'0" x 5'8"	5.4 x 1.2 m	17'7" x 4'0"
Weight	2530 Kgs	5580 lbs	3170 Kgs	6988 lbs	5300 Kgs	11660 lbs	7600 Kgs	16758 lbs
Lifting Capacity	317 Kgs	700 lbs	350 Kgs	771 lbs	360 Kgs	800 lbs	500 Kgs	1102 lbs

This range of machines cater for external rough terrain applications. All models are 4 wheel drive and have stabilisers to allow the machine to be levelled on uneven ground.



## Diesel Scissor Lifts

10.0m - 18.0m working heights

	SJ6826		SL30		SJ6832		SJ8841		GS5390	
Diesel	✓		✓		✓		✓		✓	
Non-Marking Tyres	✗		✗		✗		✗		✗	
4x4 Rough Terrain	✓		✓		✓		✓		✓	
Levelling Capability	✓		✓		✓		✓		✓	
Narrow	✗		✗		✗		✗		✗	
Reach Height	9.9 m	32' 6"	11.0 m	36' 6"	11.8 m	38' 8"	14.5 m	47' 6"	18.0 m	59'
Platform Height	7.9 m	25' 11"	9.0 m	30' 0"	9.8 m	32' 2"	12.5 m	41' 0"	16.0 m	53'
Stowed Height Closed	1.6 m	5' 3"	2.6 m	8' 7"	1.8 m	5' 11"	2.2 m	7' 2"	2.47 m	8' 2"
Length	2.7 m	8' 11"	4.4 m	14' 4"	2.7 m	8' 11"	3.5 m	11' 5"	6.57 m	21' 7"
Width	1.7 m	5' 7"	1.9 m	6' 2"	1.7 m	5' 7"	2.2 m	7' 2"	2.29 m	7' 7"
Platform Size	1.4 x 2.4 m	4'7" x 7'11"	4.2 x 1.5 m	13'8" x 5'0"	1.4 x 2.4 m	4'7" x 7'11"	3.4 x 1.7 m	11'2" x 5'6"	1.83 x 3.98 m	6' x 13' 1"
Platform Size Ext.	1.4 x 3.9m	4' 7" x 12' 10"	n/a	n/a	1.4 x 3.9m	4' 7" x 12' 10"	4.6 x 1.7 m	15'1" x 5'6"	1.83 X 6.57 m	6' x 21' 7"
Weight	2903 Kgs	6400 lbs	2785 Kgs	6140 lbs	3475 Kgs	7661 lbs	5212 Kgs	11490 lbs	7574 Kgs	16698 lbs
Lifting Capacity	567 Kgs	1250 lbs	450 Kgs	95 lbs	454 Kgs	1001 lbs	454 Kgs	1000 lbs	680 Kgs	1500 lbs

## IPAF Training Courses...

We offer training courses that instruct how to prepare and safely operate all the machines in this brochure. IPAF categorise the equipment, and on completion of your course you are issued a certificate valid for five years that details which of the categories you are trained to operate.

The IPAF training categories are as follows:

**1a – Static Vertical (1a, 1a+)**

**1b – Static Boom (1b, 1b+)**

**3a – Mobile Vertical (3a, 3a+)**

**3b – Mobile Boom (3b, 3b+)**



# LIFT

The IPAF training categories, with abbreviations and brief explanations, are:

**Static Vertical (1a, 1a+):** Vertical personnel platforms (static)

**Static Boom (1b, 1b+):** Self-propelled booms (outriggers), trailers/push-arounds, vehicle-mounted platforms

**Mobile Vertical (3a, 3a+):** Scissor lifts, vertical personnel platforms (mobile)

**Mobile Boom (3b, 3b+):** Self-propelled booms



Our IPAF Scissor & Boom Operator training courses cover all categories, however we also offer refresher courses if there's just one or two categories that you need to brush up on.

Give our Training Personnel a call today for more information or to book a course!

call **0 3 3 0 3 3 3 4 8 4 8**

or visit **www.gtaccess.co.uk**





This range of machines are designed with small footprints for internal or external use where space is restricted.



## Compact Electric Booms

10.0m - 16.0m working heights

	STAR 10		Z30		HR12		AB38		HR15	
Battery	✓		✓		✓		✓		✓	
Non-Marking Tyres	✓		✓		✓		✓		✓	
4x4 Rough Terrain	✗		✗		✗		✗		✗	
Narrow	✓		✓		✓		✓		✓	
Jib Boom	✓		✓		✗		✗		✓	
Reach Height	10.0 m	32' 9"	10.8 m	35' 4"	12.2 m	40' 0"	13.5 m	44' 6"	15.7 m	51' 7"
Platform Height	8.0 m	26' 3"	8.8 m	28' 10"	10.2 m	33' 6"	11.5 m	37' 9"	13.7 m	45' 1"
Max. Horiz. Reach	3.1 m	10' 2"	6.3 m	20' 8"	6.1 m	20' 0"	6.1 m	20' 0"	9.6 m	31' 6"
Height Closed	2.0 m	6' 6"	2.0 m	6' 6"	1.9 m	6' 3"	2.0 m	6' 6"	2.2 m	7' 2"
Length	2.6 m	8' 8"	5.3 m	17' 5"	4.1 m	13' 5"	4.0 m	13' 2"	6.5 m	21' 5"
Width	1.0 m	3' 3"	1.2 m	3' 11"	1.5 m	4' 11"	1.5 m	4' 11"	1.5 m	4' 11"
Platform Size	1.0 x 0.8 m	3'3" x 2'6"	1.2 x 0.8 m	3'11" x 2'6"	1.1 x 0.6 m	3'7" x 2'2"	1.2 x 0.6 m	3' 1" x 2'2"	1.8 x 0.7 m	5'11" x 2'4"
Weight	2760 Kgs	6085 lbs	6622 Kgs	14600 lbs	3060 Kgs	6750 lbs	3850 Kgs	8490 lbs	6100 Kgs	13450 lbs
Lifting Capacity	200 Kgs	440 lbs	225 Kgs	500 lbs	200 Kgs	440 lbs	215 Kgs	474 lbs	225 Kgs	500 lbs



This range of machines are designed for the industrial market for internal and external applications. They combine an on-board battery system as well as a diesel engine, the user simply selects the appropriate power source for the location.



## Bi-Energy Booms

12.0m - 28.0m working heights

	HR12BI		HR15BI		Z45BI		HR17BI		M600		HR21BI		HR28BI	
Battery	✓		✓		✓		✓		✓		✓		✓	
Diesel	✓		✓		✓		✓		✓		✓		✓	
Non-Marking Tyres	✓		✓		✓		✓		✓		✓		✓	
4x4 Rough Terrain	✗		✗		✗		✗		✓		✗		✓	
Narrow	✓		✓		✗		✓		✗		✗		✗	
Jib Boom	✗		✓		✓		✓		✓		✓		✓	
Reach Height	12.2 m	40' 0"	15.7 m	51' 7"	16.0 m	52' 6"	17.2 m	56' 5"	20.29 m	66' 0"	20.7 m	68' 0"	28.0 m	92'
Platform Height	10.2 m	33' 6"	13.7 m	45' 1"	14.0 m	46' 0"	15.2 m	49' 10"	18.29 m	60' 0"	18.7 m	61' 4"	26.0 m	85' 6"
Max. Horiz. Reach	6.1 m	20' 0"	9.6 m	31' 6"	7.6 m	25' 1"	9.6 m	31' 6"	13.06 m	42' 10"	12.6 m	41' 4"	19.0 m	62'
Height Closed	1.9 m	6' 3"	2.2 m	7' 2"	2.1 m	6' 11"	2.1 m	6' 11"	2.57 m	8' 5"	2.2 m	7' 0"	2.7 m	8' 10"
Length	4.1 m	13' 5"	6.5 m	21' 5"	6.8 m	22' 5"	6.3 m	20' 8"	9.37 m	30' 9"	6.3 m	20' 6"	9.28 m	30' 5"
Width	1.5 m	4' 11"	1.5 m	4' 11"	1.8 m	6' 0"	1.5 m	4' 11"	2.44 m	8' 0"	2.3 m	7' 5"	2.49 m	8' 2"
Platform Size	1.1 x 0.6 m	3'7" x 2'2"	1.8 x 0.7 m	5'11" x 2'4"	1.8 x 0.7 m	5'11" x 2'4"	1.5 x 0.7 m	4'11" x 2'4"	1.83x0.76m	6'0" x 2'6"	1.8 x 0.7 m	5'11" x 2'4"	2.4 x 0.9 m	7'10" x 2'11"
Weight	3060 Kgs	6750 lbs	6100 Kgs	13450 lbs	7620 Kgs	16800 lbs	7200 Kgs	15900 lbs	6759 Kgs	14900 lbs	6350 Kgs	14000 lbs	14500 Kgs	32000 lbs
Lifting Capacity	200 Kgs	440 lbs	225 Kgs	500 lbs	225 Kgs	500 lbs	225 Kgs	500 lbs	230 Kgs	500 lbs	225 Kgs	500 lbs	280 Kgs	620 lbs



This particular range of machines are all 4 wheel drive for the most demanding external applications. This gives them unrivalled ability to be driven across rough unfinished ground, though they still need to work from a fairly level base. Articulated booms offer superior up & over reach capabilities.



## Diesel Articulated Booms

	HR12RT		HR15RT		Z45RT		Z51RT		MAN160	
Diesel	✓		✓		✓		✓		✓	
Non-Marking Tyres	✓		✓		✗		✗		✗	
4x4 Rough Terrain	✓		✓		✓		✓		✓	
Narrow	✓		✓		✗		✗		✗	
Jib Boom	✗		✓		✓		✓		✓	
Reach Height	12.2 m	40' 0"	15.7 m	51' 7"	16.0 m	52' 6"	17.6 m	57' 9"	16.25 m	53' 4"
Platform Height	10.2 m	33' 6"	13.7 m	45' 1"	14.0 m	46' 0"	15.6 m	51' 3"	14.25 m	46' 10"
Max. Horiz. Reach	6.1 m	20' 0"	9.6 m	31' 6"	7.6 m	25' 1"	9.2 m	30' 4"	9.1 m	29' 11"
Height Closed	1.9 m	6' 3"	2.2 m	7' 2"	2.1 m	6' 11"	2.2 m	7' 1"	2.37 m	7' 8"
Length	4.1 m	13' 5"	6.5 m	21' 5"	6.8 m	22' 5"	7.5 m	24' 6"	7.0 m	23' 0"
Width	1.5 m	4' 11"	1.5 m	4' 11"*	2.3 m	7' 6"	2.3 m	7' 6"	2.3 m	7' 7"
Platform Size	1.1 x 0.6 m	3'7" x 2'2"	1.8 x 0.7 m	5'11" x 2'4"	1.8 x 0.7 m	5'11" x 2'4"	1.8 x 0.7 m	5'11" x 2'4"	1.8 x 0.8 m	5'11" x 2'8"
Weight	3060 Kgs	6750 lbs	6100 Kgs	13450 lbs	7620 Kgs	16800 lbs	7212 Kgs	15900 lbs	7450 Kgs	16423 lbs
Lifting Capacity	200 Kgs	440 lbs	225 Kgs	500 lbs	225 Kgs	500 lbs	225 Kgs	500 lbs	230 Kgs	507 lbs





## 12.0m - 28.0m working heights

	MAN160+		MAN180		MAN200		HR21		HR28	
Diesel	✓		✓		✓		✓		✓	
Non-Marking Tyres	✗		✗		✗		✗		✗	
4x4 Rough Terrain	✓		✓		✓		✓		✓	
Narrow	✗		✗		✗		✗		✗	
Jib Boom	✓		✓		✓		✓		✓	
Reach Height	16.25 m	53' 4"	17.65 m	57' 11"	20.0 m	65' 7"	20.7 m	68' 0"	28.0 m	92' 0"
Platform Height	14.25 m	46' 10"	15.65 m	51' 5"	18.0 m	59' 1"	18.7 m	61' 4"	26.0 m	85' 6"
Max. Horiz. Reach	9.1 m	29' 11"	10.6 m	34' 10"	12.0 m	39' 4"	12.6 m	41' 4"	19.0 m	62' 0"
Height Closed	2.37 m	7' 8"	2.53 m	8' 4"	3.15 m	10' 4"	2.2 m	7' 0"	2.7 m	8' 10"
Length	7.0 m	23' 0"	7.77 m	25' 6"	8.5 m	27' 11"	6.3 m	20' 6"	9.28 m	30' 5"
Width	2.3 m	7' 7"	2.3 m	7' 7"	2.4 m	7' 11"	2.3 m	7' 5"	2.49 m	8' 2"
Platform Size	1.8 x 0.8 m	5' 11" x 2' 8"	1.8 x 0.8 m	5' 11" x 2' 8"	2.1 x 0.8 m	6' 11" x 2' 8"	1.8 x 0.7 m	5' 11" x 2' 4"	2.4 x 0.9 m	7' 10" x 2' 11"
Weight	7450 Kgs	16423 lbs	8090 Kgs	17836 lbs	10000 Kgs	22047 lbs	6350 Kgs	14000 lbs	14500 Kgs	32000 lbs
Lifting Capacity	400 Kgs*	882 lbs	230 Kgs	507 lbs	230 Kgs	507 lbs	225 Kgs	500 lbs	280 Kgs	620 lbs

\* EXTRA LIFTING CAPACITY



This range of machines are all 4 wheel drive for the most demanding external applications. This gives them unrivalled ability to be driven across rough unfinished ground, though they still need to work from a fairly level base. Straight telescopic booms have greater outreach than articulated booms.



## Diesel Telescopic Booms

20.0m - 28.0m working heights

	M600		S60		S65		SJ66		S85	
Diesel	✓		✓		✓		✓		✓	
Non-Marking Tyres	✓		✗		✗		✗		✗	
4x4 Rough Terrain	✓		✓		✓		✓		✓	
Narrow	✗		✗		✗		✗		✗	
Jib Boom	✓		✗		✓		✓		✓	
Reach Height	20.29 m	66' 0"	20.3 m	66' 0"	21.8 m	71' 6"	22.12 m	72' 7"	27.9 m	91' 6"
Platform Height	18.29 m	60' 0"	18.3 m	60' 0"	19.8 m	65' 0"	20.12 m	66' 0"	25.9 m	85' 0"
Max. Horiz. Reach	13.06 m	42' 10"	15.5 m	50' 10"	17.1 m	56' 2"	17.37 m	56' 12"	23.3 m	76' 6"
Height Closed	2.57 m	8' 5"	2.72 m	8' 11"	2.7 m	8' 10"	2.57 m	8' 5"	2.8 m	9' 2"
Length	9.37 m	30' 9"	8.51 m	27' 11"	9.5 m	31' 2"	10.34 m	33' 11"	12.2 m	40' 0"
Width	2.44 m	8' 0"	2.49 m	8' 2"	2.5 m	8' 1"	2.44 m	8' 0"	2.5 m	8' 1"
Platform Size	1.83 x 0.76 m	6'0" x 2'6"	1.83 x 0.76 m	6'0" x 2'6"	1.8 x 0.7 m	5'11" x 2'4"	0.91 x 1.83 m	3'0" x 6'0"	1.8 x 0.7 m	5'11" x 2'4"
Weight	6759 Kgs	14900 lbs	9728 kgs	21455 lbs	10024 Kgs	22100 lbs	13110 Kgs	28903 lbs	17236 Kgs	38000 lbs
Lifting Capacity	230 Kgs	500 lbs	227 Kgs	500 lbs	225 Kgs	500 lbs	227 Kgs	500 lbs	225 Kgs	500 lbs



This range of machines are ideal for multi-site work as they can be towed behind your vehicle. They also are very quick to set up on sloping ground with their powered outriggers.



## Trailer Mounted Booms

12.0m - 17.0m working heights

	NL120T		NL170		NL210	
Battery	available in bi-energy		available in bi-energy		available in bi-energy	
Diesel	✓		✓		✓	
Non-Marking Tyres	✗		✗		✗	
4x4 Rough Terrain	✗		✗		✗	
Narrow	✓		✗		✗	
Jib Boom	✗		✗		✗	
Reach Height	12.2 m	40' 0"	17.1 m	56' 1"	21.0 m	69' 0"
Platform Height	10.2 m	33' 6"	15.1 m	49' 6"	19.0 m	62' 6"
Max. Horiz. Reach	6.1 m	20' 1"	8.7 m	28' 6"	12.0 m	39' 6"
Height Closed	1.9 m	6' 3"	2.15 m	7' 0"	2.27 m	7' 5"
Length	4.5 m	14' 9"	6.2 m	20' 4"	6.95 m	22' 10"
Width	1.1m*in transit	4' 11" *in transit	1.65m*in transit	5' 5" *in transit	1.8m*in transit	5' 11" *in transit
Platform Size	1.1 x 0.6 m	3'7" x 2'2"	1.1 x 0.6 m	3'7" x 2'2"	1.4 x 0.7 m	4'7" x 2'4"
Weight	1400 Kgs	3080 lbs	1900 Kgs	4180 lbs	3495 Kgs	7700 lbs
Lifting Capacity	200 Kgs	440 lbs	200 Kgs	440 lbs	225 Kgs	500 lbs

\* 3.55m / 11' 8" in Operation

\* 4.4m / 14' 5" in Operation

\* 4.3m / 14' 1" in Operation





This range of machines are designed for the application when a standard machine will not suffice. Whether it be ground conditions, restricted access, weight loadings or just the height needed, one of these platforms will hopefully resolve your issue.



## Specialist Access Platforms

## 12.0m - 23.0m working heights

	SD120		GL1470		SD170		GL1780		LL2010		SD210		LL2312	
Battery	available in bi-energy		mains 110v		✓		mains 110v		✗		✗		mains 110v	
Diesel	✓		✓		✓		✓		✓		✓		✓	
Non-Marking Tyres	✗		✗		✗		✗		✗		✓		✗	
4x4 Rough Terrain	✓		✓		✓		✓		✓		✓		✓	
Narrow	✗		✓		✗		✓		✗		✗		✓	
Jib Boom	✗		✓		✗		✓		✓		✓		✓	
Tracks	✗		✓		✗		✓		✓		✗		✓	
Reach Height	12.65 m	41' 7"	14.0 m	45' 9"	17.1 m	56' 1"	16.91 m	55' 5"	20.0 m	65' 7"	21.3 m	70' 0"	23.0 m	75' 6"
Platform Height	10.65 m	34' 11"	11.94 m	39' 2"	15.1 m	49' 6"	14.91 m	48' 8"	18.0 m	59' 1"	19.3 m	63' 4"	21.0 m	68' 9"
Max. Horiz. Reach	6.1 m	20' 0"	7.0m/5.61m	22'11"/18'5"	8.7 m	28' 7"	6.78m/8.02m	22'3"/26'3"	9.7 m	31' 10"	12.6 m	41' 4"	11.5m/10.0m	37'9"/32'10"
Height Closed	2.0 m	6' 7"	2.0 m	6' 6"	2.1 m	6' 11"	1.98 m	6' 5"	1.99 m	6' 7"	2.25 m	7' 5"	2.03m	8' 9"
Length	3.9 m	12' 10"	4.0 m	13' 1"	5.6 m	18' 4"	4.53 m	14' 9"	5.0 m	16' 5"	6.15 m	20' 2"	5.96 m	19' 6"
Width	1.6m* in transit	5' 3"* in transit	0.8m* in transit	2'6"* in transit	1.6m* in transit	5'3"* in transit	0.79m* in transit	2' 6"* in transit	1.1 m	3' 8"	2.05m* in transit	6'9"* in transit	990 mm	3' 3"* in transit
Platform Size	1.1 x .065m	3'7" x 2'2"	1.5 x 0.8 m	4'9" x 2'6"	1.1 x 0.65m	3'7" x 2'2"	0.65 x 1.3 m	2' 1" x 4' 3"	1.3 x .069m	4'3" x 2'3"	1.5 x 0.7 m	4'11" x 2'4"	1.4 x 0.7 m	4'3" x 2'4"
Weight	2260 Kgs	4980 lbs	1700 Kgs	3748 lbs	2750 Kgs	6000 lbs	2080 Kgs	4586 lbs	2880 Kgs	6350 lbs	3950 Kgs	8700 lbs	3100 Kgs	6834 lbs
Lifting Capacity	200 Kgs	440 lbs	120/200Kgs	265/440 lbs	200 Kgs	440 lbs	120/200Kgs	265/440 lbs	230 Kgs	507 lbs	225 Kgs	500 lbs	120/200 Kgs	265/440 lbs

\*3.2m/10'6" in Operation

\*2.8m/9'2" in Operation

\*4.4m/14'5" in Operation

\*2.89m/9'5" in Operation

\*4.2m/13'9" in Operation

\*3.98m/12'11" in Operation



Notes





## Contact

### BROMSGROVE

**t:** 01527 871123  
**f:** 01527 873075  
**e:** bro@gtaccess.co.uk

**a:** 19-21 Sherwood Road  
Aston Fields  
Industrial Estate  
Bromsgrove  
Worcestershire  
B60 3DR

### GLOUCESTER

**t:** 01452 725903  
**f:** 0870 762 6343  
**e:** glo@gtaccess.co.uk

**a:** Unit 3a  
Quedegeley Trading  
Estate East  
Haresfield  
Gloucester  
GL10 3EX

### HEREFORD

**t:** 01432 359555  
**f:** 01432 352080  
**e:** her@gtaccess.co.uk

**a:** The Corral  
Watery Lane Farm  
Watery Lane  
Hereford  
HR2 6JW

### SHREWSBURY

**t:** 01952 897972  
**f:** 01952 897982  
**e:** shr@gtaccess.co.uk

**a:** Unit 5  
Lancaster Road  
Shrewsbury  
SY1 3LG

### STOKE ON TRENT

**t:** 08453 720 302  
**f:** 08453 720 312  
**e:** sto@gtaccess.co.uk

**a:** Unit 5 Home Farm  
Nelson Industrial Estate  
West Avenue  
Talke  
Stoke on Trent  
ST7 1TZ

\*Standard rates apply

call **0 3 3 0 3 3 3 4 8 4 8**\* or visit **www.gtaccess.co.uk**



Follow us on Facebook - GTAccess Ltd • Check out our Facebook & Twitter pages for last minute booking deals!



Twitter @gtaccessltd